

LESEN PENSIJILAN BARANGAN

Product Certification Licence



SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada
SIRIM QAS International Sdn. Bhd. hereby grants to

TROCELLEN S. E. A. SDN. BHD.
LOT 2213, BATU 9
KEBUN BARU, JALAN KASAWARI
42500 TELOK PANGLIMA GARANG
SELANGOR, MALAYSIA

Lesen untuk menggunakan Tanda Pensijilan di atas barangan
a licence to use the Certification Mark on

REFLECTIVE INSULATION

Please refer to detail in the SCHEDULE


sebagai mematuhi keperluan

as complying with

MS 2095 : 2014



Mohd Azanuddin bin Salleh
Ketua Pegawai Eksekutif
Chief Executive Officer
SIRIM QAS International Sdn. Bhd.



SIRIM QAS International Sdn. Bhd.
(No. Syarikat 410334-X)
1, Persiaran Dato' Menteri
Seksyen 2, Peti Surat 7035
40700 Shah Alam
Selangor Darul Ehsan
MALAYSIA.

Tel : 60-3-55446400
Faks : 60-3-55446466

<http://www.sirim.my>
<http://www.malaysiancertified.com.my>

Tarikh Mula Pensijilan : 20 January 2017

Certified Since

Sah Sehingga : 20 January 2021

Valid Until

Tarikh Dikeluarkan : 03 January 2020

Issue Date

No Siri : 051852

Serial No

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.

SCHEDULE

TROCELLEN S. E. A. SDN. BHD.



Trade Mark : TROCELLEN PRO
Model : 2506W3CF4 733 + ALU-S, 2512W3CF4 733 + ALU-S, 2530W3CF4L 733 + ALU-S
Foam Density: 25 kg/m³, Grammage, kg/m²: 0.291 - 0.965
Rating : Heavy Duty, Medium Vapour Barrier, Reflective Emittance, Fire Propagation Index:
5.6, 4.0, 7.7, Surface Spread of Flame: Class One,
Thermal Resistance, m²K/W: 1.081, 1.26 & 1.33
Type : Foam base
Size : Thickness: 6mm – 30mm
Test report no.: 2016CE1230, 2016FE0108, 2016FE0109, 2016CE1231,
2016FE0253, 2016FE0107, 2016CE1232, 2016FE0254, 2016FE0105

Trade Mark : TROCELLEN PRO
Model : 3305NF4 775 + ALU-S, 3310NF4 775 + ALU-S, 3312NF4 775 + ALU-S
Foam Density: 33 kg/m³, Grammage, kg/m²: 0.285 - 0.498
Rating : Extra Heavy Duty, Medium Vapour Barrier, Reflective Emittance, Fire Propagation
Index: 6.9, 8.5, 5.9, Surface Spread of Flame: Class One, Thermal Resistance,
m²K/W: 0.731, 1.102 & 1.136
Type : Foam base
Size : Thickness: 5mm – 12mm
Test report no.: 2016CE0851, 2016FE0102, 2016FE0103, 2016CE1233,
2016FE0100, 2016FE0101, 2016CE1234, 2016FE0252, 2016FE0099

Trade Mark : TROCELLEN PRO
Model : Trocellen Pro – AirPro Plus
Foam Density: 25 kg/m³, Grammage, kg/m²: 0.259 - 1.110
Rating : Light Duty, Medium Vapour Barrier, Reflective Emittance, Fire Propagation Index:
6.6, 7.5 & 9.8, Surface Spread of Flame: Class One, Thermal Resistance, m²K/W:
1.543, 1.413 & 1.223
Type : Foam Base
Size : Thickness: 6mm – 30mm
Test report no.: 2018CE1197, 2018FE0590, 2018FE0591, 2018CE1500,
2018FE0675, 2018FE0676, 2019CE1002, 2019FE0449, 2019FE0450

End of page